



## Motor: MI82 4P

Referência do Motor  Código Code	Potência Power		Corrente Current	Dimensões Dimensions			
	In (W)	Out (W)	A	Ø (mm)	P (mm)	C (mm)	A (mm)
513	29	5	0,21	6,35	13	50	79
514	36	5	0,26	6,35	13	50	79
719	40	7	0,24	6,35	19	50	85
1019	43	10	0,25	6,35	19	50	85
1219	54	12	0,35	6,35	19	50	85
1625	70	16	0,45	8	25,4	55	95
2032	70	20	0,54	8	25,4	60	102
2538	100	25	0,75	8	32	70	115
3444	110	34	0,82	8	39	83	131
4050	130	40	1,00	9,5	44,5	89	137

Motores de indução tipo pólos amortecidos.  
 Monofásico de 4 pólos, 220-240V, 50-60Hz, 1.300 r.p.m.  
 Execução fechada, funcionamento em todas as posições.  
 Tampas de cobertura em alumínio.  
 Veio montado sobre casquilhos autolubrificantes, com reserva de óleo. Isolamento classe "B".  
 Para trabalhar com temperaturas ambiente de -30°C a +40°C  
 Por encomenda: 110V-a 240V; 60Hz  
 APLICAÇÕES: sistemas de refrigeração, congelação e conservação.

Single phase, 4 shaded pole motors, 220-240V, 50-60Hz, 1.300 r.p.m.  
 Close type, all position mounting. Aluminium shields.  
 Self-aligning sleeve bearings, permanently lubricated.  
 Class "B" insulation.  
 Suitable for room temperatures from -30°C to +40°C  
 By request: voltage from 110V-to 240V, 60Hz.  
 Three-core cable.  
 APLICATIONS: Cooling, freezing and storing systems, hair drivers, welding machines.

TELF 244 841 714  
 FAX. 244 840 169

EMAIL- SILMOTOR@SAPO.PT



**5w**

---



**7w**

---



**10w**

---



**16w**

---



**20w**

---



**25w v1**

---



**25w v2**

---



**34w**

---



**40w**